

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

IN THE CLAIMS:

A detailed listing of all claims that are, or were, in the application follows:

-- No New Amendments --

The following is a clean copy of all claims as they currently stand in the Application, including Examiners amendments of November 2, 2004.

1. (previously presented): A manufactured firelog providing consumer selected control of burning rate, comprising:

a combustible material agglomerated into a shape having top and bottom surface configured for supporting the firelog during combustion and dimensioned for use as a combustible firelog;

a flammable wrapper surrounding said combustible firelog; and

at least one combustion shield joined to said flammable wrapper adjacent said top or bottom surface to reduce the air reaching a portion of the surface of said combustible firelog;

wherein said combustion shield comprises a fireproof or fire resistant material;

wherein consumer positioning of said combustible firelog for burning with said combustion shield retained underneath said combustible firelog shields that portion of said combustible material from air to reduce the burning rate; and

wherein burning of said combustible firelog with said combustion shield retained on an upper portion of said combustible firelog allows the combustion shield to separate from the combustible firelog as said wrapper burns so that the combustion shield does not substantially impact burning rate.

2. (previously presented): A manufactured firelog as recited in claim 1, wherein said combustion shield is adapted with apertures disposed on at least portions of its surface which increase the available combustible firelog surface area in relation to a combustion shield without said apertures.

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

3. (previously presented): A manufactured firelog as recited in claim 1:
wherein said combustion shield is configured to allow full or partial removal at consumer's discretion to expose additional portions of said firelog prior to burning;
wherein the rate of combustion is selected by said consumer prior to igniting said firelog, in response to orientation of said firelog and the extent, if any, of discretionary combustion shield removal.

4. (previously presented): A manufactured firelog as recited in claim 3, further comprising means for grasping attached to said combustion shield to facilitate full or partial removal of said shield.

5. (previously presented): A manufactured firelog having an adjustable combustion rate, comprising:

combustible material agglomerated into a combustible firelog; and
means for selectively shielding an exterior surface portion of said firelog from combustion during a portion of the time that said firelog is being burned;
wherein said selective shielding means is configured to selectively change the combustion rate of said firelog by restricting the airflow reaching portions of the surface of the firelog;

wherein a consumer can select the amount of shielding retained under said firelog.

6. (previously presented): A manufactured firelog as recited in claim 5:
wherein said means for selectively shielding said firelog comprises a combustion shield of a fire-resistant or fireproof material;
wherein said combustion shield is positioned proximal to said firelog to restrict airflow from reaching portions of the surface of the firelog to reduce the resulting combustion rate;
wherein said selective shielding means is configured so that when it is not oriented

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

under said firelog during combustion, the shielding means falls away as the surrounding portions of the wrapper burn away.

7. (original): A manufactured firelog as recited in claim 6, wherein said combustion shield comprises a metallic foil material.

8. (original): A manufactured firelog as recited in claim 7, wherein said metallic foil is less than approximately 30 mils thick.

9. (previously presented): A manufactured firelog as recited in claim 6, wherein said combustion rate may be adjusted by positioning at least a portion of said combustion shield on the underside of said firelog.

10. (previously presented): A manufactured firelog as recited in claim 6, wherein said combustion shield is attached to the surface of said firelog.

11. (previously presented): A manufactured firelog as recited in claim 6, wherein said combustion shield is joined to a flammable wrapper surrounding said firelog.

12. (previously presented): A manufactured firelog as recited in claim 9, wherein said combustion shield further comprises means for grasping configured for allowing a consumer to fully or partially remove said combustion shield to alter the combustion rate.

13. (canceled).

14. (previously presented): In a manufactured firelog having a combustible material that has been formed into a shape dimensioned for use as a combustible firelog, wherein the improvement comprises:

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

forming said manufactured firelog as a plurality of separate complementary shapes configured for arrangement in a nested combination during burning;
surrounding each complementary shape with a flammable wrapper; and
wherein the complementary shapes may be burned separately to provide one level of heat output and fire duration, or nested together in combination to provide a second level of heat output and fire duration.

Claims 15-50 (Canceled).

51. (previously presented): In a manufactured firelog formed from an agglomeration of combustible material in a shape dimensioned for use as a combustible firelog product, wherein the improvement comprises:

incorporating a combustion shield of a fire-resistant or fireproof material positioned to cover a portion of the surface of said firelog to restrict air from reaching portions of the surface of the firelog to reduce the combustion rate;

wherein said firelog is configured so that said combustion shield can be oriented under said firelog to provide a first burning rate, or oriented in other positions to provide a second burning rate which is higher than said first burning rate.

52. (previously presented): The manufactured firelog as recited in claim 51, wherein said combustion shield comprises a flexible metallic foil attached to a flammable wrapper surrounding said firelog.

53. (previously presented): The manufactured firelog as recited in claim 52, wherein said combustion shield is configured for full or partial removal from said firelog to alter the amount of firelog surface area being covered by said combustion shielding thereby altering the resulting combustion rate.

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

Claims 54 - 56: (Canceled).

57. (previously presented): A manufactured firelog as recited in claim 1, wherein said combustion material comprises combustible materials, binding agents, and solid combustion aids.

58. (previously presented): A manufactured firelog as recited in claim 1, wherein combustion shield attached to the wrapper is configured to fall away from the firelog as the surrounding portions of the wrapper are burned away.

59. (previously presented): A manufactured firelog as recited in claim 5, wherein the surface area of the shield retained under the firelog can be selected by the consumer in response to orienting of the firelog and shield means to select the extent, if any, that the shielding means is retained beneath the underside of the firelog.

60. (previously presented): A manufactured firelog as recited in claim 59, wherein said combustible firelog is configured so that said selective shielding means can be oriented under said firelog to provide a first burning rate, or oriented away from the underside of the firelog to provide a second burning rate which is higher than said first burning rate.

61. (previously presented): A manufactured firelog, comprising:
a combustible material formed into a first firelog portion of a first shape; and
a combustible material formed into a second firelog portion of a second shape;
wherein said second shape is configured for being nested with said first shape;
a combustible wrapper separately covering each of said first and said second firelogs;

whereby the nested combination of first and second firelog portions may be burned as a single unit or separated from one another and either firelog portion burned individually.

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

62. (previously presented): A manufactured firelog as recited in claim 61, further comprising means for separably adhering the wrapper of said first firelog with the nested configuration with said second firelog.

63. (previously presented): A manufactured firelog having a selectable combustion rate, comprising:

- a combustible material agglomerated into a shape having top and bottom surface configured for supporting the firelog during combustion and dimensioned for use as a combustible firelog;

- a flammable wrapper surrounding said combustible firelog;

- at least one combustion shield joined to said flammable wrapper adjacent said top or bottom surface to reduce the air reaching a portion of the surface of said combustible firelog;

- wherein said combustion shield comprises a fire proof or fire resistant material;

- wherein said combustion shield is adapted with apertures disposed on at least portions of its surface which increase the available combustible firelog surface area in relation to a combustion shield without said apertures;

- wherein consumer positioning of said combustible firelog for burning with said combustion shield retained underneath said combustible firelog shields that portion of said combustible material from air to reduce the burning rate; and

- wherein burning of said combustible firelog with said combustion shield retained on an upper portion of said combustible firelog allows the combustion shield to separate from the combustible firelog as said wrapper burns so that the combustion shield does not substantially impact burning rate.

64. (previously presented): A manufactured firelog as recited in claim 63, wherein said combustion shield is configured to allow full or partial removal at consumer's discretion

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

to expose additional portions of said firelog prior to burning.

65. (previously presented): A manufactured firelog as recited in claim 64, further comprising means for facilitating the full or partial removal of said combustion shield.

66. (previously presented): A manufactured firelog having a selectable combustion rate, comprising:

a combustible material agglomerated into a combustible firelog; and
means for selectively shielding an exterior surface portion of said firelog from combustion during a portion of the time that said firelog is being burned;

wherein said selective shielding means is configured as fire-resistant or fireproof material positioned proximal to said firelog to selectively change the combustion rate of said firelog by restricting the airflow reaching portions of the surface of the firelog;

wherein a consumer can select the amount of shielding retained under said firelog.

67. (previously presented): A manufactured firelog as recited in claim 66, wherein said combustion shield comprises a metallic foil material.

68. (previously presented): A manufactured firelog as recited in claim 66, wherein said combustion shield is attached to the surface of said firelog.

69. (previously presented): A manufactured firelog as recited in claim 66, wherein said combustion shield is joined to a flammable wrapper surrounding said firelog.

70. (previously presented): A manufactured firelog as recited in claim 66, further comprising means for facilitating the full or partial removal of said combustion shield.

71. (previously presented): A manufactured firelog having a selectable combustion rate, comprising:

a combustible material agglomerated into a combustible firelog; and
means for selectively shielding an exterior surface portion of said firelog from combustion during a portion of the time that said firelog is being burned;

wherein said selective shielding means is configured as fire-resistant or fireproof material positioned proximal to said firelog to selectively change the combustion rate of said firelog by restricting the airflow reaching portions of the surface of the firelog;

wherein a consumer can select the amount of shielding retained under said firelog;

wherein said selective shielding means is joined to a flammable wrapper surrounding said firelog and configured so that when it is not oriented under said firelog during combustion, the shielding means falls away as the surrounding portions of the wrapper burn away.

72. (previously presented): A manufactured firelog as recited in claim 71, wherein said combustion shield comprises a metallic foil material.

73. (previously presented): A manufactured firelog as recited in claim 71, further comprising means for facilitating the full or partial removal of said combustion shield.

74. (previously presented): A manufactured firelog having a selectable combustion rate, comprising:

combustible material agglomerated into a combustible firelog; and
means for selectively shielding an exterior surface portion of said firelog from combustion during a portion of the time that said firelog is being burned;

wherein said selective shielding means is configured to selectively change the combustion rate of said firelog by restricting the airflow reaching portions of the surface of the firelog;

wherein a consumer can select the amount of shielding retained under said firelog in response to orienting the firelog and shield means to select the extent, if any, that the shielding means is retained beneath the underside of the firelog.

75. (previously presented): A manufactured firelog as recited in claim 74, wherein said combustion shield comprises a metallic foil material.

76. (previously presented): A manufactured firelog as recited in claim 74, wherein said combustion shield is attached to the surface of said firelog.

77. (previously presented): A manufactured firelog as recited in claim 74, wherein said combustion shield is joined to a flammable wrapper surrounding said firelog.

78. (previously presented): A manufactured firelog as recited in claim 74, further comprising means for facilitating the full or partial removal of said combustion shield.

79. (previously presented): A manufactured firelog having a selectable combustion rate, comprising:

combustible material agglomerated into a combustible firelog;

means for selectively shielding an exterior surface portion of said firelog from combustion during a portion of the time that said firelog is being burned;

wherein said selective shielding means is configured to selectively change the combustion rate of said firelog by restricting the airflow reaching portions of the surface of the firelog;

wherein a consumer can select the amount of shielding retained under said firelog;
and

wherein consumer selection of the orientation of said shielding means under said firelog provides a first burning rate, while orienting said shielding means away from the

underside of the firelog provides a second burning rate which is higher than said first burning rate.

80. (previously presented): The manufactured firelog as recited in claim 14, further comprising means for separably adhering the wrappers of said separate complementary shapes in their nested configuration.

81. (previously presented): A manufactured firelog having a selectable combustion rate, comprising:

a combustible material formed into a plurality of separate complementary shapes configured for arrangement in a nested combination during burning;

a flammable wrapper surrounding each complementary shape configured to allow nesting of the separately wrapped complementary shapes during burning; and

wherein the complementary shapes may be burned separately to provide one level of heat output and fire duration, or nested together in combination to provide another level of heat output and fire duration.

82. (previously presented): A manufactured firelog as recited in claim 81, further comprising means for separably adhering the wrappers of said separate complementary shapes in their nested configuration.

83. (previously presented): A manufactured firelog having a selectable combustion rate, comprising:

a combustible material formed into a first and second separate complementary shape configured for arrangement in a nested combination during burning;

a flammable wrapper surrounding each complementary shape configured to allow nesting of the separately wrapped complementary shapes during burning;

wherein said plurality of separate complementary shapes comprises first and second

Appl. No.: 10/016,852
Amdt. Dated: January 25, 2005
Office Act Date: November 8, 2004

separate firelog portions which can be arranged in a nested combination during burning;
wherein said first portion is smaller than said second portion;
wherein the first firelog portion can be burned separately to provide a first level of heat output and duration;
wherein the second firelog portion can be burned separately to provide a second level of heat output and duration;
wherein the first and second firelog portion can be burned in combination in a nested configuration to provide a third level of heat output and duration; and
wherein the first and second firelog portion can be burned un-nested, to provide a fourth level of heat output and duration.

84. (previously presented): A manufactured firelog as recited in claim 83, further comprising means for separably adhering the wrappers of said separate complementary shapes in their nested configuration.